



Urea Liquor 40%

Marine Grade Diesel Exhaust Fluid

PRODUCT SPECIFICATIONS

Parameter	Specification
Urea Concentration, wt. %	39 – 41
Refractive Index at 20 °C	1.3947 – 1.3982
Alkalinity as Ammonia, wt. %	0.5 max
Biuret, wt. %	0.8 max
Aldehydes, mg/kg	100 max
Insoluble matter, mg/kg	50 max
Phosphate (PO ₄), mg/kg	1 max
Calcium, mg/kg	1 max
Iron, mg/kg	1 max
Magnesium, mg/kg	1 max
Sodium, mg/kg	1 max
Potassium, mg/kg	1 max

Comments

Marine Grade Diesel Exhaust Fluid meets the quality requirements of ISO 18611-1.

PLEASE OBTAIN A PRODUCT SAFETY DATA SHEET FOR MORE INFORMATION. The Safety Data Sheet ("SDS") for this product contains important environmental, health and safety information regarding this product, including information concerning the handling and storage of this product. The most current version of the SDS for this product can be obtained at www.cfindustries.com or by contacting your CF representative.

WITHOUT LIMITING THE PROVISIONS OF ANY APPLICABLE SALES AGREEMENT, SELLER'S LIABILITY FOR DAMAGES OR LOSSES SHALL BE LIMITED TO REPLACEMENT OF THE PRODUCT OR REFUND OF THE PURCHASE PRICE, AT SELLER'S OPTION.